Public Joint Stock Company UFAORGSINTEZ

450037, Russian Federation, Republic of Bashkortostan, Ufa city Laboratory for the Quality Control of the Products Obtained During the Production of Ethylene Propylene Rubber CERTIFICATE No. <u>97-2021</u> Synthetic ethylene propylene diene rubber EPDM-E TS 20.17.10-100-05766563-2019

15 20.17.10-100-05766563-2019							
Grade		EPDM-E-50 group 2, 3			OKPD 2 Code:	20.17.10.173	
Batch No.		84			Date of issue, selection, analysis	30.07.2021	
Briquette quantity 220				NET weight:	5,500 kg		
Briquette numbers 19681-19900				The designation of the RD according to which the sample was taken GOST 27109			
Item	Indic	cators name	ors name		RD for test method	Norm according to	The actual
No.						TS	value
	Mooney viscosity MB 1+4 (125 °C), Mooney units, within (*)				GOST-10722	46-55	53
2.	Viscosity spread within the batch, Mooney units, maximum				.17.10-100-05766563-2019 item 5.1.0	5 5	3
3.	Mass fraction of ethylene units, %, Group 1 within Group 2 Group 3				ASTM D 3900, ,	50-58	-
				TS 20.17.10-100-05766563-2019 item 5.2	59-68	60	
						69-78	-
	The mass fractionof Group 1ethylidennorbornene, %, withinGroup 2			TS 20	.17.10-100-05766563-2019 item 5.3.2	2 1.0-3.0	-
						3.1-5.0	-
			Group 3			5.1-7.0	5.6
	Group 4					7.1-9.0	-
5.	Loss of mass on drying, %, maximum			TS 2	GOST 19338, 0.17.10-100-05766563-2019 item 5.4	0.7	0.2
6.	Mass fraction of ash, %, maximum				GOST-19816.4, 0.17.10-100-05766563-2019 item 5.5	0.2	0.05
7.	Mass fraction of vanadium, %, maximum				.17.10-100-05766563-2019 Appendix B		0.004
	Mass fraction of alcohol - toluene extract, %, maximum			TS 2	GOST 19920.6, 0,17.10-100-05766563-2019 item 5.7	4.0	1.0
9.	The mass fraction of the antioxidant Irganox-1520L, %, minimum]	rs 20.17.10-100-05766563-2019 Appendix C	0.10	0.24
10.	Conditional tensile strength with carbon grade P-324,				GOST 270,	Not standardized,	11.9
	MPa, minimum			TS 20	.17.10-100-05766563-2019 item 5.9,		
11.	Elongation at break, %, minimum				Recipe No. 2	_	370
4	le preparation at $t = 60$	0.000					-

*- sample preparation at t = 60.0 ± 5.0 °C

Conclusion: the product corresponds to TS 20.17.10-100-05766563-2019

The products are manufactured in accordance with the Management systems certified for compliance with the specifications of: ISO 9001:2015 Certificate No. 31100600 QM15, ISO 14001:2015 Certificate No. 31100600 UM15, ISO 45001: 2018 Certificate No. 31100600 OHS18.

Scope of Application:

designed for the manufacture of rubber products

Characteristics of fire and explosion hazard:

According to GOST 12.1.044, rubber belongs to the group of solid combustible materials with a high smoke-forming ability. In the process of production and processing, when rubber is heated above 230 $^{\circ}$ C, it is possible to release volatile products, including marginal (ethane, propane) and unsaturated (ethylene, propylene) hydrocarbons, carbon oxides. Upon contact with an open fire, it ignites without explosion and burns with a smoky flame with the formation of a melt and the release of the above-mentioned thermal degradation products.

Storage rules:

Store the material in paper bags with a polyethylene liner in a dry, ventilated room, excluding direct sunlight, at a distance of at least 1m from heating devices and at a temperature not higher than 30 °C:

- rubber packed in bags - in stacks no more than 1.2 m high;

- rubber packed in box pallets in stacks by 3-4 pallets in height.

Warranty period of storage: 1 year from the date of manufacture.

Engineer of the laboratory for quality control of ethylene-propylene-rubber products of the Quality Management:

(power of attorney No. 214/21 dated 27.07.2021) Certificate issue date: <u>August 02, 2021</u>

Transportation rules:

All types of transport are covered.

Type of shipment via railroad: carload. When transporting rubber packed in various types of bags in railway wagons, they are loaded into the car to full capacity without packaging.

When transporting rubber packed in box pallets in railway wagons, pallets are installed in 2-3 rows in height in accordance with the requirements of GOST 21650.

Neutralization, disposal, and burial of wastes: Waste unsuitable for recycling does not require neutralization, is subject to removal to places agreed with the bodies of the Ministry of Emergency Situations and Environmental Safety and the Federal Service for Supervision of Consumer Rights Protection and Human Welfare (Department of Rospotrebnadzor).

Signature E.O. Zubareva

Stamp here Stamp: Quality department